

Del #	Input Voltage	No. of Lamps	Lamp Watts	Input Watts	Input Current	Power Factor	Ballast Factor	THD	Bench Heat Test at 23°C Ambient Temp.	Crest Factor
6T4UYS	120	1	26W CFL	27	0.22	0.99	1.00	9.9	44°C	<1.7
	120	1	18W CFL	25.8	0.20	0.99	1.10	5.5	42°C	<1.7
	120	1	21W 2D	21.3	0.18	0.99	0.90	10	38°C	<1.7
	120	1	28W 2D	29	0.24	0.99	0.95	11.14	43°C	<1.7
	120	1	32W CFL	32	0.27	0.99	0.95	10.9	42°C	<1.7
	120	1	38W 2D	28.7	0.24	0.99	0.87	8.2	44°C	<1.7
	120	1	42W CFL	41	0.35	0.99	0.95	9.5	44°C	<1.7
	120	1	57W CFL	51	0.43	0.99	0.88	8.7	52°C	<1.7
	120	1	40W Biax L	42	0.34	0.99	1.00	8.9	45°C	<1.7
	120	1	18W Biax L	21	0.18	0.99	1.20	9.9	42°C	<1.7
	120	1	24W Biax L	26	0.21	0.99	1.10	9.9	44°C	<1.7
	120	1	36W Biax L	32	0.27	0.99	0.83	7.07	45°C	<1.7
	120	1	39W Biax L	32	0.27	0.99	0.83	7.07	45°C	<1.7
	120	1	22W T5 Circular	23.7	0.20	0.99	0.97	8.5	40°C	<1.7
	120	1	40W T5 Circular	38	0.31	0.99	0.94	9.9	48°C	<1.7
	120	2	26W CFL	53	0.45	0.99	1.00	8.2	52°C	<1.7
	120	2	18W CFL	48	0.40	0.99	1.10	2.8	42°C	<1.7
	120	2	18W Biax L	39	0.33	0.99	1.00	9.6	44°C	<1.7
	120	2	24W Biax L	47	0.39	0.99	0.95	8.8	50°C	<1.7
	120	2	22W + 40W T5 Circular	52.7	0.44	0.99	0.75	4.9	54°C	<1.7
	277	1	26W CFL	27	0.96	0.98	1.00	15.0	42°C	<1.7
	277	1	18W CFL	26.4	0.10	0.97	1.10	6.5	42°C	<1.7
	277	1	21W 2D	21.3	0.09	0.91	0.90	15.0	37°C	<1.7
	277	1	28W 2D	29	0.11	0.99	0.95	15.0	42°C	<1.7
	277	1	32W CFL	33	0.13	0.95	0.95	12.5	42°C	<1.7
	277	1	38W 2D	28.5	0.12	0.90	0.87	20.0	42°C	<1.7
	277	1	42W CFL	41	0.16	0.97	0.95	10.1	44°C	<1.7
	277	1	57W CFL	50	0.19	0.98	0.88	8.1	52°C	<1.7
	277	1	40W Biax L	41	0.15	0.96	1.00	9.5	44°C	<1.7
	277	1	18W Biax L	21	0.087	0.83	1.20	20.0	44°C	<1.7
	277	1	24W Biax L	26	0.096	0.88	1.10	20.0	42°C	<1.7
	277	1	36W Biax L	32	0.12	0.99	0.82	8.67	44°C	<1.7
	277	1	39W Biax L	32	0.12	0.99	0.82	8.67	44°C	<1.7
	277	1	22W T5 Circular	23.7	0.10	0.92	0.97	20.0	39°C	<1.7
	277	1	40W T5 Circular	38	0.14	0.96	0.95	9.9	44°C	<1.7
	277	2	26W CFL	52	0.20	0.98	1.00	9.5	44°C	<1.7
	277	2	18W CFL	46.5	0.16	0.98	1.10	4.8	42°C	<1.7
	277	2	18W Biax L	38	0.15	0.96	1.00	10.3	42°C	<1.7
	277	2	24W Biax L	46	0.17	0.97	0.95	8.6	42°C	<1.7
	277	2	22W + 40W T5 Circular	51.97	0.19	0.98	0.75	5.2	52°C	<1.7

Range:
 Voltage Range 108V-305V
 Rating: Type 1 Outdoor
 Note Wiring Length: 25 ft.
 Interference: None
 High Power Factor
Operation:
 Minimum Starting Temperature to -30°C
 Maximum Case Temperature 90°C
 UL Listed and Rated A
 Instant Start
 UL Listed, cUL Certified, HL Certified
 PCB's
 Class P Thermally Protected
 Surge Protected - Meets ANSI and IEC
 EMI/RFI: meets FCC Part 18 Subpart E
 Short Circuit Protection / Auto Shut Off
 Automatic Reset Thermal Shutdown Switch

Physical Parameters:
 Length: 5.0"
 Width: 2.32"
 Height: 1.0"
 Weight: 0.53 lbs.
Mounting Length 4.65"
 Bottom Mount w/Studs
 - AC-2/26T4UVBMS
 With Leads - AC-2/26T4UVSL
 White 9"
 Black 9"
 Green 9"
 Red 14"
 Blue 14"
 Yellow 14"

Qty/Cartron: 40 pcs

