

























Wall Packs

Intermatic's line of HID lighting is the perfect solution for a wide variety of outdoor lighting needs. In addition, Intermatic has a full array of time switches and photo controls designed to complement any residential, commercial or industrial lighting system.

- UL listed for wet locations
- Heavy duty die-cast aluminum powder coating construction
- High-impact polycarbonate lens (WL35, WL50, WL70)


- Tempered glass lens (WL100, WL150, WL250, WL400)
- Corrosion-resistant hardware
- 1/2" tapped holes available for installing photocell (photocell optional)
- Brand name lamp included

		Model	Description	Photometric Chart
		 WL050MH	50 Watt Metal Halide Wall Pack - 120/208/240/277V A	
		 WL070MH	70 Watt Metal Halide Wall Pack - 120/208/240/277V A	
		 WL035HPS	35 Watt High Pressure Sodium Wall Pack - 120V. A	
		 WL050HPS	50 Watt High Pressure Sodium Wall Pack - 120V. A	
		 WL070HPS	70 Watt High Pressure Sodium Wall Pack - 120V. A	
		 WL100MH	100 Watt Metal Halide Wall Pack - 120/208/240/277V A	
		 WL100HPS	100 Watt High Pressure Sodium Wall Pack - 120/208/240/277V A	
		 WL150MH	150 Watt Metal Halide Wall Pack - 120/208/240/277V B	
		 WL175MH	175 Watt Metal Halide Wall Pack - 120/208/240/277V B	
		 WL150HPS	150 Watt High Pressure Sodium Wall Pack - 120/208/240/277V B	
		 WL250MH	250 Watt Metal Halide Wall Pack - 120/208/240/277V C	
		 WL250HPS	250 Watt High Pressure Sodium Wall Pack - 120/208/240/277V C	
		 WL400MH	400 Watt Metal Halide Wall Pack - 120/208/240/277V C	
		 WL400HPS	400 Watt High Pressure Sodium Wall Pack - 120/208/240/277V C	

Photometric Data

Chart A

70W HPS at 10' Mounting Height




Multiples of Mounting Height

Mounting Height	Multiplier	Watts	HPS	MH
8'	2.4m	1.60	35	.4
10'	3.1m	1.00	50	.6
12'	3.7m	.70	70	1.0
16'	5.0m	.40	100	1.5
20'	6.2m	.25		1.4

Chart B

150W HPS at 10' Mounting Height




Multiples of Mounting Height

Mounting Height	Multiplier	Watts	HPS	MH
8'	2.4m	1.60	70	.4
10'	3.1m	1.00	100	.6
12'	3.7m	.70	150	1.0
16'	5.0m	.40	175	—
20'	6.2m	.25		.9

Chart C

250W HPS at 16' Mounting Height



Multiples of Mounting Height

Mounting Height	Multiplier	Watts	HPS	MH
8'	2.4m	4.0	250	1.0
10'	3.1m	2.6	400	1.8
12'	3.7m	1.8		1.2
16'	5.0m	1.0		
20'	6.2m	.6		
24'	7.5m	.5		
32'	10m	.3		